ASK nano 4K (USB-C)






Key Features

- Plug and play
- App Free
- Support iOS/Android/Windows system
- Share the images and audio from smart-phone camera or to the large display simultaneously
- Auto selection of the best Wi-Fi channel to ensure smooth streaming
- Come with the fast 802.11ac MIMO technology to increases Wi-Fi speeds
- 4K60 high resolution quality
- HDCP supported to ensure data security
- USB- C interface of the video source must support the DP protocol (DisplayPort)

Application







Dimension


TX:








RX:











unit:mm

Order Codes

Product Code	Item
450-2003-01-0	ASK nano 4K (USB-C)

Tel: +86-592-5771197 | Fax: +86-592-5788216 | E-mail: sales@rgblink.com

Headquarter: Room 601A, No. 37-3 Banshang community, Building 3, Xinke Plaza, Torch Hi-Tech Industrial Development Zone, Xiamen, China





Specification

TX	Interface	Input	1×USB-C	
		Power	1×USB-C (reverse powering supported)	
	LED	Red and Blue		
	Power	DC 5V/1A		
	Consumption	5W		
	Dimension	93mm×28.3mm×13mm (cable excluded)		
	Weight	50g		
RX	Interface	Output	1×HDMI-A	
		Power	1×USB-C	
	Standards	HDMI	2.0	
	LED	Red and Blue		
	Power	DC 5V/1A		
	Consumption	3W		
	Dimension	83mm×32mm×13mm		
	Weight	30g		
Performance	Video Input	up to 3840×2160@30		
	Video Output	up to 3840×2160@60		
	Audio	PCM		
	Wireless Channel	IEEE 802.11ac, 5GHz		
	Latency	about 100ms		
	Security	AES 128 bit		
	Platform Supported	Windows, iOS, Android system and any devices with HDMI jack		
	Distance	About 30 meters in the clear line of sight		
Environment	Operating Environment	Operating Temperature	0°C ~ +40°C (+32°F to +104°F)	
		Operating Humidity	10% ~ 80% RH	
	Storage Environment	Storage Temperature	-10°C ~ +60°C (+14°F to +140°F)	
		Storage Humidity	5% ~ 90% RH	
-	1	+		

Tel: +86-592-5771197 | Fax: +86-592-5788216 | E-mail: sales@rgblink.com

Headquarter: Room 601A, No. 37-3 Banshang community, Building 3, Xinke Plaza, Torch Hi-Tech Industrial Development Zone, Xiamen, China

